

# MATERIAL SAFETY DATA SHEET (MSDS)

## VISION LE100 & LE200 FLUID

**1. Identification of the Chemical Product:**

White Mineral Oil, CAS Number 8042-47-5

**2. Name & Address of the Supplier in Europe:**

A.C. Lighting Ltd  
Centauri House  
Hillbottom Road  
High Wycombe  
Bucks  
HP12 4HQ  
England

Telephone: +44 (0)1494 446000  
Fax: +44 (0)1494 461024  
Email: [sales@aclighting.co.uk](mailto:sales@aclighting.co.uk)  
Internet: <http://www.aclighting.co.uk>

**3. Identification of Any Dangers:**

Inhaled: Acute exposure may result in bronchial irritation  
Absorbed through skin: Chronic exposure may cause contact or eczematous dermatitis  
Swallowed: May cause diarrhoea

**4. Description of First Aid Treatment to be Given in Case of Emergency:**

Eye Contact: Wash eyes with large amounts of water/saline solution occasionally lifting upper & lower eyelids until evidence of chemical is clear.  
Skin Contact: Wash with soap & water.  
Inhaled: Remove to fresh air.  
Swallowed: No specific antidote. Treat symptomatically and supportively.

**5. Fire Precautions:**

Flash Point: Greater than 176 degrees Centigrade (closed cup)  
Fire Extinguishing: Dry chemical, waterfog, CO2, foam or sand/earth.  
Closed containers exposed to fire may be cooled with water.

**6. Measures to be Taken in Case of Spillage:**

Shut off leak and dyke up large spills. Absorb with an inert material such as sand, earth or vermiculite. Sweep up and dispose of in accordance with local regulations.

**7. Precautions to be Taken in Storage & Handling:**

Keep away from heat & flames. Do not store near strong oxidising agents such as hydrogen peroxide, bromide and chromic acid. The maximum storage temperature is 66 degrees Centigrade.

**8. Precautions for Workers to Follow when Handling:**

Respiratory Protection: Under normal use none.  
When concentrations are above 5mg per cubic meter an approved air respirator.

Protective Clothing: Wear oil impervious clothing. Avoid wearing clothing soaked with mineral oil.  
Wear appropriate protective gloves to avoid skin contact.  
Always wear splash proof goggles when dealing with spills

Ventilation: Always ensure adequate ventilation to meet permissible exposure limits (PEL)

**9. Physical & Chemical Properties**

Formula: A mixture of liquid hydrocarbons refined from petroleum.  
Chemical Name: White Mineral Oil  
Toxic or hazardous Ingredients: None  
Odour, Appearance, Colour & Form: An odourless clear viscous liquid.  
Specific Gravity: Less than 1.0 (water = 1.0)  
Vapour Pressure: In mmHg @ 20 degrees Centigrade – Less than 0.5mm  
Boiling Point: Greater than 230 degrees Centigrade  
Melting Point: Not applicable. Does not melt down under heat.  
Evaporation rate: Nil @ 25 degrees Centigrade. (butyl acetate = 1.0)

**10. Stability & Reactivity:**

Keep away from strong oxidisers such as hydrogen peroxide, bromide and chromic acid.

**11. Toxicological Information:**

Non toxic.

**12. Ecological Information:**

No data available.  
As the substance is not soluble in water do not flush into water or waste system.

**13. Information Concerning Disposal of Waste Product:**

Dispose of in accordance with all local regulations.

**14. Information Concerning Transport of Product:**

Department of Transport: Non regulated.  
Reportable Quantity: None  
Freight Classification: 65 Petroleum Oil  
Special Transportation Notes: None

**15. Information Regarding Conformity to Relevant Regulations:**

No data available for Europe.  
The fluid meets the requirements of the US Food & Drug Administration CFR 172.878  
The fluid is not suspected to be a cancer agent.